

Reeling Hose

APPLICATIONS

- ⇒ For hose reels on road tankers for metered delivery of household and automotive fuel.

ADVANTAGES

- ⇒ A light weight, flexible hose, highly resistant to abrasion.
- ⇒ Static electricity dissipated by conductive braid.
- ⇒ Can be supplied ready fitted with swaged gun-metal couplings, sealing caps or kink resisting spring wire guards.
- ⇒ Hose assemblies are individually tested and can be supplied with a hydrostatic proof test certificate in accordance with the regulations.



TECHNICAL DESCRIPTION

- ⇒ Inner tube: oil and petrol resistant NBR/PVC, black, smooth.
- ⇒ Reinforcement: synthetic textile, braided.
- ⇒ Cover: oil and weather resistant NBR/PVC, red, smooth.
- ⇒ Temperature range: -30°C TO +55°C.
- ⇒ Electrical properties: built-in-wire for discharge of static electricity.

STANDARD APPROVAL EN 1360:2013 type 1.

TECHNICAL SPECIFICATIONS

OIL & GAS

ID mm	Wall Thickness mm	OD mm	Working Pressure BAR	Burst Pressure BAR	Bending Radius mm	Weight kg/m	Length m	Article Number	Min Order m
35.0 +0.8	6.5	48.0 +1.0	16	48	110	1.11	50	5602765	600
35.0 +0.8	6.5	48.0 +1.0	16	48	110	1.11	60	5602766	600
38.0 +0.8	7.25	52.5 +1.0	16	48	115	1.39	50	5513199	600
38.0 +0.8	7.25	52.5 +1.0	16	48	115	1.39	60	5513200	600

Tolerance on length: ±1% (ISO 1307 Standard).