



PVC hose with rigid PVC spiral, for delivery and suction of food liquids.



SMOOTH SURFACES



FLEXIBILITY



ABRASION RESISTANCE



TEMPERATURE RANGE

-5°C +60°C
23°F +140°F



CHEMICAL RESISTANCE

PVC table



CRUSHING RESISTANCE



FOR FOOD

Suitable according to Reg. CE 1935/2004 and Reg. UE 10/2011 for contact with foodstuff that requires a simulating liquid type A B C, migration tests performed at 40°C for 24 hours.

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS		BENDING RADIUS	WORKING PRESSURE 1:3 23° C	BURSTING PRESSURE 23° C	VACUUM 23° C	Ø RIGID SPIRAL (AXB IF OVAL)	SPIRAL PIT CH	SPIRAL DIRECTION	COIL LENGTH	AVAILABILITY
			mm	g/m									
inch	mm	mm	mm	g/m	mm	bar	bar	m h2o	mm	mm		m	
	18	24	3	230	65	8	24	7	2,3x3,5	6.5	right	50	ON DEMAND
3/4	19	24.6	2.8	230	70	8	24	7	2,5x3,5	7	right	50	ON DEMAND
	20	26.2	3.1	275	75	8	24	7	2,5x4	6.7	right	50	IN STOCK
1	25	31.6	3.3	330	120	8	24	7	3,2x3,4	7.4	right	50	IN STOCK
	30	37	3.5	420	140	7	21	7	3,4x3,6	7.5	right	50	IN STOCK
1 1/4	32	39.2	3.6	460	150	7	21	7	3,4x3,6	7.7	right	50	IN STOCK
	35	41.8	3.4	500	160	7	21	7	3,4x3,6	7.7	right	50	IN STOCK
1 1/2	38	45.4	3.7	550	170	6.5	19.5	7	3.6	7.6	right	50	IN STOCK
	40	47.6	3.8	610	180	6.5	19.5	7	3.6	7.8	right	50	IN STOCK
1 3/4	45	52.8	3.9	670	200	6.5	19.5	7	3.6	8	right	50	IN STOCK
2	50	58.2	4.1	810	220	6	18	7	4	8.3	right	50	IN STOCK
2	51	59.5	4.1	810	225	6	18	7	4	8.5	right	50	ON DEMAND
	55	63.6	4.3	860	250	6	18	7	4	9.8	right	50	ON DEMAND
	60	69	4.5	970	270	5	15	7	4.4	8.3	right	50	IN STOCK
2 1/2	63	71.5	4	1040	290	5	15	7	3.9	8.5	right	50	IN STOCK
	70	79.2	4.6	1200	320	4	12	7	4.3	9	right	50	IN STOCK
	75	85.4	5.2	1380	350	4	12	7	4.8	9.5	right	50	IN STOCK
	80	90.6	5.5	1560	360	4	12	7	5	10.5	right	25	IN STOCK
3 1/2	90	100.4	5.2	1800	430	4	12	7	5.1	10.3	right	25	IN STOCK
	100	112	6	2160	480	4	12	7	5.5	11.3	right	25	IN STOCK
4	102	114	6.2	2160	480	4	12	7	5.5	11.3	right	25	IN STOCK
	110	122	6	2400	530	4	12	6	5.5	11.5	right	25	IN STOCK
	120	132.4	6.2	2850	680	3	9	6	6	11.5	right	25	IN STOCK
	125	137.6	6.3	3130	730	3	9	6	6.1	11.6	right	25	IN STOCK
5	127	140.6	6.8	3130	730	3	9	6	6.1	12.3	right	25	ON DEMAND
	150	164.4	7.2	4250	810	3	9	5	6.5	14	right	25	IN STOCK
6	152	167.2	7.4	4250	810	3	9	5	6.8	14.5	right	25	ON DEMAND
	200	218.2	9.1	6400	900	2	6	5	8.4	21.5	right	10	IN STOCK

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.