



PVC hose with rigid PVC spiral, for delivery and suction of liquids.



**SMOOTH SURFACES**

\*\*\*\*\*



**FLEXIBILITY**

\*\*\*\*\*



**ABRASION RESISTANCE**

\*\*\*



**TEMPERATURE RANGE**

-25°C +55°C  
-13°F +131°F



**CHEMICAL RESISTANCE**

PVC table



**CRUSHING RESISTANCE**

\*\*\*

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	BURSTING PRESSURE 23°C	VACUUM 23°C	SPIRAL PITCH	SPIRAL DIRECTION	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	m h2o	mm		m	
	<b>18</b>	24	3	230	60	6,5	19.5	7	6.5	right	50	ON DEMAND
	<b>20</b>	26.2	3.1	275	65	6,5	19.5	7	7	right	50	IN STOCK
<b>1</b>	<b>25</b>	31.6	3.3	330	100	6,5	19.5	7	7.4	right	50	IN STOCK
	<b>30</b>	37	3.5	420	125	5,5	16.5	7	7.5	right	50	IN STOCK
<b>1 1/4</b>	<b>32</b>	39.2	3.6	460	135	5,5	16.5	7	7.7	right	50	IN STOCK
	<b>35</b>	41.8	3.4	500	145	5	15.0	7	7.7	right	50	IN STOCK
<b>1 1/2</b>	<b>38</b>	45.4	3.7	550	155	4,5	13.5	7	7.6	right	50	IN STOCK
	<b>40</b>	47.6	3.9	610	160	4,5	13.5	7	7.8	right	50	IN STOCK
<b>1 3/4</b>	<b>45</b>	52.8	3.9	670	180	4	12.0	7	8	right	50	IN STOCK
<b>2</b>	<b>50</b>	58.2	4.1	810	200	3,5	10.5	7	8.3	right	50	IN STOCK
<b>2</b>	<b>51</b>	59.5	4.1	810	225	3,5	10.5	7	8.5	right	50	ON DEMAND
	<b>55</b>	63.6	4.3	860	225	3,5	10.5	7	9.8	right	50	ON DEMAND
	<b>60</b>	69	4.5	970	245	3,5	10.5	7	8.3	right	50	IN STOCK
<b>2 1/2</b>	<b>63</b>	71.5	4	1040	260	3,5	10.5	7	8.5	right	50	IN STOCK
	<b>70</b>	79.2	4.6	1200	290	3,5	10.5	7	9	right	50	ON DEMAND
	<b>75</b>	85.4	5.2	1380	315	2,5	7.5	7	9.5	right	50	IN STOCK
<b>3</b>	<b>76</b>	86.2	5	1380	320	2,5	7.5	7	12	right	50	IN STOCK
	<b>80</b>	90.6	5.3	1560	325	2,5	7.5	7	10.5	right	25	IN STOCK
<b>3 1/2</b>	<b>90</b>	100.4	5.2	1800	390	2,5	7.5	7	10.3	right	25	ON DEMAND
	<b>100</b>	112	6	2160	430	2,5	7.5	7	11.3	right	25	ON DEMAND
<b>4</b>	<b>102</b>	114	6.2	2160	430	2,5	7.5	7	11.3	right	25	IN STOCK
	<b>110</b>	122	6	2400	480	2,5	7.5	5	11.5	right	25	ON DEMAND
	<b>120</b>	132.4	6.2	2850	610	2,5	7.5	5	11.5	right	25	ON DEMAND
	<b>125</b>	137.6	6.3	3130	660	2	6.0	5	11.6	right	25	ON DEMAND
<b>5</b>	<b>127</b>	140.6	6.8	3130	670	2	6.0	5	12.3	right	25	IN STOCK
	<b>150</b>	164.4	7.2	4250	730	2	6.0	5	14	right	25	ON DEMAND
<b>6</b>	<b>152</b>	167.2	7.4	4250	750	2	6.0	5	14.5	right	25	IN STOCK
	<b>200</b>	218.2	9.1	6400	810	1	3.0	5	21.5	right	25	ON DEMAND

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.