



Flexible layflat PVC hose, with polyester yarn reinforcement resistant to elongation, for pressurised delivery of liquids in general.



SMOOTH SURFACES



FLEXIBILITY

*



ABRASION RESISTANCE



TEMPERATURE RANGE

-5°C +60°C
23°F +140°F



CHEMICAL RESISTANCE

PVC table



CRUSHING RESISTANCE

*

Ø I.D.	Ø I.D.	Ø O.D.	WALL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	WORKING PRESSURE 40°C	BURSTING PRESSURE 23°C	TENSILE BREAKING LOAD	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	bar	kg	m	
	25	27	1	115		7	4.0	21.0	224	50-100	ON DEMAND
	32	34	1	150		7	4.0	21.0	288	50-100	ON DEMAND
	38	40	1	210		5	3.0	15.0	335	50-100	ON DEMAND
	40	42	1	225		5	3.0	15.0	350	50-100	ON DEMAND
	51	54	1,5	280		5	3.0	15.0	445	50-100	ON DEMAND
	60	63	1,5	350		4	2.4	12.0	495	50-100	ON DEMAND
	63	66	1,5	370		4	2.4	12.0	530	50-100	ON DEMAND
	76	79	1,5	475		4	2.4	12.0	625	50-100	ON DEMAND
	80	83	1,5	490		4	2.4	12.0	655	50-100	ON DEMAND
	102	105.5	1,6	650		4	2.4	12.0	830	50-100	ON DEMAND
	152	156	2	1250		3	1.8	9.0	1250	50-100	ON DEMAND
	204	209	2,5	1700		2,5	1.5	8.0	1700	50-100	ON DEMAND

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.